



- MANUFACTURED STONE
- VAPOR PERMEABLE MEMBRANE (TYP.)
- 2 LAYERS OF 60 MIN. BUILDING PAPER
- DRAINAGE MAT W/ FILTER FABRIC
- 1/2"–3/4" SCRATCH COAT W/ REINFORCING MESH
- SELF ADHESIVE MEMBRANE (TYP.)
- SEALANT JOINT AND BACKER ROD (WHERE REQUIRED AS A CONTROL JOINT)

3"  
3"



INSIDE/OUTSIDE CORNER

THIS DETAIL IS INTENDED AS A GENERAL GUIDE FOR WOOD FRAMED RESIDENTIAL BUILDINGS. IT IS NOT MEANT TO REPLACE PROJECT SPECIFIC DESIGN BASED ON THE ENVIRONMENTAL CONDITIONS AT THE SITE AND SPECIFIC MATERIALS TO BE UTILIZED IN THE ASSEMBLIES.

<b>RESIDENTIAL MASONRY CONTRACTORS ASSOCIATION</b>	
-	

<b>RMCA DETAILS</b> MANUFACTURED STONE VENEER	
DATE: 3-30-06	SCALE: N.T.S.
DESIGN:	<b>5</b>
DRAWN:	
REVIEWED:	